



GROUP |

**Cartwright Insulated
Curtain Sider**

Trailers Built for Australia

STANDARD FEATURES

Trailer Lengths, widths, heights
and axle configurations
available to suit all operations



Trailers Built for Australia

Cartwright Transport PTY Ltd
www.cartwright-group.com.au
+61 [0]411 176 033
howard-hansen@cartwright-group.com.au
PO Box 251, Wentworth Falls NSW 2782

Chassis	Main Beam - Painted beam automatically welded incorporating high tensile steel top and bottom flanges Cross Bearers - Corrosion resistant cold rolled structural steel I bearers bolted to main chassis beam Side Rave - 126mm deep corrosion resistant	Under-run	Galvanised bolt on under-run assembly
Fifth Wheel	Rubbing Plate - 140mm deep high tensile steel neck with 8mm rub plate assembly and bolt in king pin Lead up - Plate angled at the front of the trailer	Side-guards	Galvanised hinged drop arms with aluminium anodised side guard rails
Landing Gear	Jost landing leg with compensating feet	Spray Suppression	Mudguards - Thermoplastic mudwings Mudflaps - Clearpass flaps
Suspension and Axles	Axles - Disc & drum axles - BPW/SAF Raise & Lower - Valve with auto reset fitted as standard	Front Bulkhead	Hot dip galvanized heavy duty pressed steel frame outer pillars design to receive fridge unit. 70mm deep insulated bulkhead with GRP faced plywood panel. 160mm x 6mm kickplate full width with pallet stops to aid air return.
Wheels and Tyres	Rims - Steel wheels in pre-finished silver (alloy options) Tyres - Twin & single tyres available to suit	Rear Frame	Hot dip galvanized bolted steel frame, 125 x65 PFC corner pillars. Double doors 80mm insulated and triple door seals with Stainless steel door furniture, double locking bars and 4 off hinges per door. Chain and clip retention. Double roller buffers fitted with D-shaped rubber profile between rollers. Bunching straps to rear corner pillars for cargo straps set at 1800mm from floor level.
Braking System and Park Brake	4S2M EBS braking system including roll stability and electronic load sensing with dedicated ISO 7638 socket Park & Shunt - Park safe valve Brake Chambers - Spring brake chambers fitted to both axles Coupling Box - Fixed front coupling box	Roof Insulation	One piece 110mm insulated roof white GRP external and internal lining. Black neoprene outer pelmet seal white internal fitted. 5mm steel top pillar protection plates. 4 x Labcraft lamps fitted in roof offset down length of roof. Switch mounted externally next to raise lower valve.
Electrics	Main Loom - 24v ISO. Plug & Play IP67 rated wiring loom (multi voltage) Front Marker - LED surface mounted and protected Rear Marker - LED surface mounted and protected Side Markers - LED Rear Cluster - LED (options available)	Curtains	Insulated EN12642XL rated PVC curtains with external labels showing whole vehicle compliance. Standard Colour: Silver RAL9006 I Strap in pocket type latch pull stainless steel locking curtain buckles, easy glide top rollers.
		Floor	Insulated floor 120mm deep. Full chequer plate 5 bar overlay. Drain holes with tubes at rearmost corners of floor.
		Load Securing	Alluminium angled cargo tracks set to face out positioned directly inboard of cant rails c/w 32 off cargo straps (options available)
		Fridge	ThermoKing SLX44e or Carrier Vector 1950 complete with 200 litre diesel tank dual fitted behind landing legs

Cartwright offer a huge amount of options to build to your exacting specifications

Get in touch with your sales rep today to discuss extra features